

Specifications

Eaton SMS4R1

Panel mount receptacle; SMS4R1



Photo is representative

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Souriau SMS series quick mating plastic rectangular connector |
| CATALOG NUMBER | SMS4R1 |
| PRODUCT LENGTH/DEPTH | 25 mm |
| PRODUCT HEIGHT | 15.2 mm |
| PRODUCT WIDTH | 21.2 mm |
| PRODUCT WEIGHT | 3 g |



Product specifications

ENVIRONMENTAL

REACH

Resources

DRAWINGS

[SMS-SE72097.pdf](#)

| | |
|------------------------------------|-------------------------------------|
| CONDITIONS | Flammability rating UL94 V0 RoHS |
| CONNECTOR ACCESSORY OPTION | No backshell possibility |
| CONNECTOR TYPE | Receptacle |
| CONTACT DELIVERY | Not delivered |
| CONTACT TYPE | Crimp |
| COUPLING TYPE | Push-Pull |
| DEGREE OF PROTECTION | IP30 |
| LAYOUT | 4 |
| SHELL MATERIAL | Plastic |
| OPERATING TEMPERATURE - MAX | 125 °C |
| OPERATING TEMPERATURE - MIN | -55 °C |
| RECEPTACLE TYPE | Front Mount Panel |
| NUMBER OF CONTACTS | 4 |
| NUMBER OF CAVITY #16 | 4 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

