

Specifications

Eaton SMS4GE3

Straight boardmount with female PCB contacts; SMS4GE3



Photo is representative

General specifications

PRODUCT NAME	Eaton Souriau SMS series quick mating plastic rectangular connector
CATALOG NUMBER	SMS4GE3
PRODUCT LENGTH/DEPTH	13.4 mm
PRODUCT HEIGHT	21.3 mm
PRODUCT WIDTH	5.9 mm
PRODUCT WEIGHT	3.5 g



Product specifications

ENVIRONMENTAL

RoHS

Resources

DRAWINGS

[BSA20236200300.pdf](#)

CONDITIONS	REACH Flammability rating UL94 V0
CONNECTOR ACCESSORY OPTION	No backshell possibility
CONNECTOR TYPE	Receptacle
CONTACT DELIVERY	Loaded
CONTACT GENDER	Socket (Female)
CONTACT PLATING	Gold
CONTACT TYPE	PCB
COUPLING TYPE	Push-Pull
DEGREE OF PROTECTION	IP30
LAYOUT	4
SHELL MATERIAL	Plastic
OPERATING TEMPERATURE - MAX	125 °C
OPERATING TEMPERATURE - MIN	-55 °C
RECEPTACLE TYPE	Front Mount Panel
NUMBER OF CONTACTS	4
NUMBER OF CAVITY #16	4

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

